

Material Safety Data Sheet

Page 1 of 3

Infosafe No. 2BKLK Issue Date: July 2003 ISSUED by BOSTIK

Product Name: **INSTANT PRO SHEET VINYL ADHESIVE**

Classified as hazardous according to criteria of NOHSC

COMPANY DETAILS

Company Name BOSTIK FINDLEY AUSTRALIA PTY LTD (ABN 003 893 838)
Address 51 - 71 High Street Thomastown
VIC 3074
Tel/Fax Tel: 03 9279 9333 Fax: 03 9279 9270

IDENTIFICATION

Product Name INSTANT PRO SHEET VINYL ADHESIVE**Proper Shipping Name** None Allocated

Other Names	Name	Mancode
	Instant Pro Sheet Vinyl Adh., 4lt	294004
	Instant Pro Sheet Vinyl Adh., 10lt	294012

UN Number None Allocated**DG Class** None Allocated**Packing Group** None Allocated**Hazchem Code** None Allocated**Poisons Schedule** Not Scheduled**Product Use** A trowellable water based adhesive.

Physical Data

Appearance Thick off-white paste with slightly sweet odour.**Melting Point** 0°C (water)**Boiling Point** 100°C (water)**Vapour Pressure** Not available**Specific Gravity** approx. 1.2**Flash Point** Non applicable**Flamm. Limit LEL** Not applicable**Solubility in Water** Soluble

Other Properties

Volatile Component approx 35%

Ingredients

Ingredients	Name	CAS	Proportion
	Rosin	8050-09-7	1-10 %
	Aldehyde/thiozoline biocide		0.1-1 %
	Ingredients determined not to be hazardous		to 100%
	Chlorothanlonil fungicide		0.1-1 %

HEALTH HAZARD INFORMATION

Health Effects

Acute - Swallowed May cause irritation to the mucous membranes.**Acute - Eye** May be an eye irritant.**Acute - Skin** May cause skin irritation.**Acute - Inhaled** Inhalation of high concentrations of vapours may cause irritation of the respiratory tract.

Continued on next page

Material Safety Data Sheet

Page 2 of 3

Infosafe No. 2BKLK Issue Date: July 2003

ISSUED by BOSTIK

Product Name: **INSTANT PRO SHEET VINYL ADHESIVE**

Classified as hazardous according to criteria of NOHSC

Chronic Repeated or prolonged skin contact may cause irritation. The rosin component has been reported to cause allergic skin reaction (sensitisation) in susceptible individuals under certain non-industrial exposure conditions of repeated and prolonged skin contact.

First Aid

Swallowed If swallowed, give patient water to drink and seek medical advice.

Eye Flush with large amounts of water for at least 15 minutes. Seek medical attention.

Skin Remove contaminated clothing and footwear. Wash affected area with plenty of soap and water. If irritation occurs seek medical attention. Launder clothing before re-use.

Inhaled Should inhalation occur remove patient to fresh air and seek medical advice.

First Aid Facilities Eye wash, safety shower.

Advice to Doctor

Advice to Doctor Treat symptomatically.

Other Health Hazard Information

PRECAUTIONS FOR USE

Exposure Limits No exposure standard is available for the material as such.

Eng. Controls Use in a well ventilated area.

Personal Protection

Protective Equip. The following personal protective equipment is recommended:
Impervious gloves.
Safety glasses.

Flammability

Fire Hazards Dried material is combustible.

SAFE HANDLING INFORMATION

Storage and Transport

Storage and Transport Store in a cool, dry place away from direct sunlight and frost. Avoid extremes of temperature. Keep containers sealed when not in use. Keep away from strong acids.

Proper Shipping Name None Allocated

Spills and Disposal

Spills & Disposal Clean-up personnel to wear personal protection. Contain spill with absorbent such as sand, earth, vermiculite or sawdust. Prevent run-off into drains and water-ways. Pump spillage into empty drums then absorb remainder. Collect impregnated absorbent into clearly labelled containers for disposal as per statutory regulations. Flush area with water.

Fire/Explosion Hazard

Fire/Explos. Hazard If dried material burns, fire-fighting personnel to wear self-contained breathing apparatus and protective clothing.
Hazardous decomposition products on burning: oxides of carbon, smoke and other toxic fumes.
Extinguishing media: water for dried polymer film.

Hazardous Reaction Incompatible with strong acids and alkalis, oxidising and reducing agents and materials which react with water.

Continued on next page

Material Safety Data Sheet

Page 3 of 3

Infosafe No. 2BKLK Issue Date: July 2003

ISSUED by BOSTIK

Product Name: **INSTANT PRO SHEET VINYL ADHESIVE**

Classified as hazardous according to criteria of NOHSC

Hazchem Code None Allocated

OTHER INFORMATION

Toxicology No toxicity data is available for this material as such.
Environ. Protection This material may be hazardous to the environment, do not discharge to drains or water-ways.
Risk Statement R43 May cause sensitization by skin contact.
Safety Statement S2 Keep out of reach of children.
S24 Avoid contact with skin.
S37 Wear suitable gloves.
Hazard Category Irritant
Technical Data Refer Product Information Bulletin
Other Information N/A - None Assigned
NOHSC - National Occupational Health & Safety Commission (Worksafe Aust.)

CONTACT POINT

Contact & 24 hour Emergency Telephone
Regulatory Affairs Officer
ph (03) 9279 9320 or
mobile 0419 335 187
...End Of MSDS...