

Material Safety Data Sheet

Page 1 of 3

Infosafe No. 2BKL7 Issue Date: July 2003 DRAFT by BOSTIK

Product Name: **INSTANT PRO CARPET & VINYL PRESSURE SENSITIVE ADHESIVE**

Not classified as hazardous according to criteria of NOHSC

COMPANY DETAILS

Company Name BOSTIK FINDLEY AUSTRALIA PTY LTD (ABN 003 893 838)
Address 51 - 71 High Street Thomastown
VIC 3074
Tel/Fax Tel: 03 9279 9333 Fax: 03 9279 9270

IDENTIFICATION

Product Name INSTANT PRO CARPET & VINYL PRESSURE SENSITIVE ADHESIVE
Proper Shipping Name None Allocated
Other Names

<u>Name</u>	<u>Mancode</u>
Instant Pro Carpet & Vinyl PS Adh., 4lt	293970
Instant Pro Carpet & Vinyl PS Adh., 10lt	293962

UN Number None Allocated
DG Class None Allocated
Packing Group None Allocated
Hazchem Code None Allocated
Poisons Schedule Not Scheduled
Product Use A water based adhesive designed for bonding vinyl tiles via trowel application.

Physical Data

Appearance Smooth, thick white paste with sweet odour.
Melting Point 0°C (water)
Boiling Point 100°C (water)
Vapour Pressure Not available
Specific Gravity 1.06-1.08 g/cm³
Flash Point Non applicable
Flamm. Limit LEL Not applicable

Other Properties

Other Information Solubility in Water (g/L): completely dispersible

Ingredients

<u>Ingredients</u>	<u>Name</u>	<u>CAS</u>	<u>Proportion</u>
	Acrylic copolymer		30-60 %
	Phthalate plasticiser		1-10 %
	Additives		1-2 %
	Water		to 100%

HEALTH HAZARD INFORMATION

Health Effects

Acute - Swallowed May cause nausea.
Acute - Eye May cause irritation.
Acute - Skin May cause skin irritation.
Acute - Inhaled Inhalation exposure not expected at ambient temperatures.
Chronic Repeated or prolonged skin contact may cause irritation.

First Aid

Continued on next page

Material Safety Data Sheet

Page 2 of 3

Infosafe No. 2BKL7 Issue Date: July 2003

DRAFT by BOSTIK

Product Name: **INSTANT PRO CARPET & VINYL PRESSURE SENSITIVE ADHESIVE**

Not classified as hazardous according to criteria of NOHSC

Swallowed	If swallowed, give patient a glass of water to drink and seek medical advice.
Eye	Hold eyelids open and flush with large amounts of water for at least 15 minutes. Seek medical attention.
Skin	Remove contaminated clothing and footwear. Wash affected area with plenty of soap and water before material dries. Dried material may be removed with skin cleanser. If irritation occurs seek medical attention. Launder clothing before re-use.
Inhaled	Should inhalation occur remove patient to fresh air and seek medical advice.
First Aid Facilities	Eye wash, safety shower.

Advice to Doctor

Advice to Doctor Treat symptomatically.

Other Health Hazard Information

PRECAUTIONS FOR USE

Exposure Limits No exposure standard is available for the material as such.
Eng. Controls Use in a well ventilated area.

Personal Protection

Protective Equip. Avoid contact with skin and eyes and avoid breathing vapours. The following personal protective equipment is recommended:
Respiratory protection if exposed to spray mists.
Impervious gloves.
Safety glasses.

Flammability

Fire Hazards Dried material is combustibile.

SAFE HANDLING INFORMATION

Storage and Transport

Storage and Transport Store in a cool, dry place away from direct sunlight and heat. Avoid extremes of temperature. Keep containers sealed when not in use. Store in corrosion proof containers.

Proper Shipping Name None Allocated

Spills and Disposal

Spills & Disposal Clean-up personnel to wear personal protection. Contain spill with absorbent such as sand, earth, vermiculite or sawdust. Prevent run-off into drains and water-ways. Pump spillage into empty drums then absorb remainder. Collect impregnated absorbent into clearly labelled containers for disposal as per statutory regulations. Flush area with water.

Fire/Explosion Hazard

Fire/Explos. Hazard If dried material burns, fire-fighting personnel to wear self-contained breathing apparatus and protective clothing. Hazardous decomposition products on burning: oxides of carbon, smoke and other toxic fumes.
Extinguishing media: water for dried polymer film.

Hazardous Reaction Incompatible with strong oxidising agents, acids and nitrates.

Hazchem Code None Allocated

Continued on next page

Material Safety Data Sheet

Page 3 of 3

Infosafe No. 2BKL7 Issue Date: July 2003

DRAFT by BOSTIK

Product Name: **INSTANT PRO CARPET & VINYL PRESSURE SENSITIVE ADHESIVE**

Not classified as hazardous according to criteria of NOHSC

OTHER INFORMATION

Toxicology No toxicity data is available for this material as such.
Environ. Protection This material may be hazardous to the environment, do not discharge to drains or water-ways.
Technical Data Refer Product Information Bulletin
Other Information N/A - None Assigned
NOHSC - National Occupational Health & Safety Commission (Worksafe Aust.)

CONTACT POINT

Contact & 24 hour Emergency Telephone
Regulatory Affairs Officer
ph (03) 9279 9320 or
mobile 0419 335 187
...End Of MSDS...