

technical data sheet

BOSTIK INSTANT-PRO™

EXTERIOR WALL & FLOOR TILE ADHESIVE

PRODUCT

Bostik Instant-PRO™ Exterior Wall & Floor Tile Adhesive is a high strength waterproof polyurethane based adhesive. It is multipurpose as it can be used for both walls and floors and also for internal and external use.

DESCRIPTION

An exceptionally high strength, high quality, waterproof polyurethane based adhesive developed to bond all types of ceramic tiles. Ideal for bonding Monocottura, Porcellanato and Bicottura tiles as well as slate, quarry tiles, terracotta tiles, mosaic tiles, granite and marble onto rigid surfaces.

RECOMMENDED USES

- Walls and floors / inside and outside the home
- Kitchens, bathrooms, verandahs, paths, feature walls, pots, mosaic tables, swimming pools, ponds
- Recommended for concrete surfaces, cement render, brickwork

FEATURES AND BENEFITS

- Easy to spread
- Ready to use – no mixing
- High strength
- No odour
- Internal and external applications
- Wall & floor applications
- Economical
- Non toxic

PROPERTIES

Appearance	White paste
Colour	White
Chemical Type	Polyurethane – major use:- adhering tiles onto walls & floors
Specific Gravity	1.35Kg/L
Working Temp	5°C - 50°C
Tack free work time	15 mins @ 20°C
Coverage	12mm x 12mm trowel approximately 6kg per m ² , 6mm x 6mm trowel approximately 3kg per m ²
Cure Time	24 hours at 23°C
Shelf Life	Unopened containers can be stored off the floor for up to 12 months in a cool, dry, weatherproof environment

PACKAGING

4 kg and 15kg pails

APPLICATION INSTRUCTIONS

1. All surfaces must be firm, rigid, clean, dry, sound and smooth. All grease, wax, oil, curing compounds, dust, plaster droppings and paint must be removed prior to the application of the adhesive.
2. Smooth steel trowel finished concrete must be primed and allowed to dry.
3. Porous surfaces should be primed. Allow concrete to cure for at least 28 days and cement render to cure for at least 7 days prior to tiling.
4. There is no need to mix any part of Exterior Wall & Floor Tile Adhesive, as it is ready to use.
5. Apply the adhesive onto the prepared substrate using a 12mm x 12mm square notched spreader for floors and 6mm x 6mm square notched spreader for walls and mosaic floor tiles. Only apply as much adhesive as can be covered prior to adhesive skinning. When laying floor tiles it is necessary to ensure that there are no voids under the tiles and that the tiles are fully supported by the adhesive.
6. The adhesive must not be disturbed for at least 24 hours at which time grouting can take place.
7. Commence grouting 24 hours after tiling.

P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

HEALTH AND SAFETY

- Wear protective gloves – PVC or similar
- Wear safety goggles
- A dust mask should be worn when handling powder
- Avoid contact with skin and eyes

CLEAN-UP

Bostik Instant-PRO™ Exterior Wall & Floor Adhesive can be removed from the face of the tiles with a damp cloth. Clean tools and equipment with warm water and detergent before glue dries.

PRECAUTIONS

- Store in a cool, dry area – off the floor
- Wear rubber gloves when handling this product
- Pot life is 2 hours at 23°C
- Only tile in small sections, as glue may dry out before tiles are laid

STORAGE

Store in a cool, dry, weatherproof environment. Can be stored in unopened containers for up to 12 months.

Note : This product is to be stored off the floor

BOSTIK INSTANT-PRO™ EXTERIOR WALL & FLOOR TILE ADHESIVE

Item No	Barcode	Stock Size	Carton Qty
294586	9310492442778	4KG	4
298557	9310492442976	15KG	1

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Findley Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK FINDLEY AUSTRALIA PTY LTD

FOR FURTHER INFORMATION



**BOSTIK FINDLEY
AUSTRALIA PTY LTD**
Phone: +61-3-9279 9333
Fax: +61-3-9279 9240

**BOSTIK FINDLEY
NZ LIMITED**
Phone: +64-4-567 5119
Fax: +64-4-567-5412

**BOSTIK FINDLEY
SINGAPORE PTE LTD**
Phone: +65-863 4088
Fax: +65-863 4077

**BOSTIK FINDLEY
(MALAYSIA) SDN BHD**
Phone: +606 764 3246
Fax: +606 764 3248

SYDNEY
Phone: 02 8825 3488
Fax: 02 8825 3411

ADELAIDE
Phone: 08 8244 0511
Fax: 08 8244 0522

PERTH
Phone: 08 9331 7666
Fax: 08 9331 7677

BRISBANE
Phone: 07 3265 2377
Fax: 07 3265 5421

(ABN 79 003 893 838)

Product:	Bostik Instant Pro™ Wall & Floor Tile Glue
Issue Date:	April 2003
Issue No:	1
Division:	Hardware