



## technical data sheet

# BOSTIK INSTANT-PRO™ PRIMER

### PRODUCT

Bostik Instant-PRO™ Primer is a liquid primer used prior to applying waterproofing and adhesive products.

### DESCRIPTION

Bostik Instant-PRO™ Primer is a synthetic, latex based liquid specifically designed for priming all porous substrates prior to the application of Bostik Instant-PRO™ Ceramic Tile Adhesive and Bostik Instant-Pro™ Waterproof It.

Bostik Instant-PRO™ Primer is recommended for use on plasterboard, fibrous cement sheet, timber, sand and cement screeds, render, concrete, brickwork and blockwork.

### RECOMMENDED USES

- Plasterboard, timber, particle board (must be sanded prior to using product) and fibrous cement sheeting must be fixed correctly
- Cement render (must be allowed to dry for at least 7 days prior to using product)
- Concrete (must be allowed to dry for at least 28 days prior to using product)

### FEATURES & BENEFITS

- Handy plastic jerry can – easy to use
- Easy to read directions and pictograms on packaging
- Makes adhesive application easy
- Reduces porosity

### PROPERTIES

Appearance	Thin liquid
Colour	White – milky
Chemical Type	Latex based liquid
Specific Gravity	1.01 Kg/L (density at 25°C)
Working Temperature	5°C to 50°C
Coverage	Approximately 8m <sup>2</sup> per litre
Cure Time	15 mins (depending upon conditions)
Shelf Life	12 months in unopened container and in cool, dry environment

### PACKAGING

1 Litre and 5 Litre Jerry Cans

### STORAGE:

Unopened containers can be stored for up to 12 months in a cool dry environment.

**Note : Prevent liquid from freezing.**

### APPLICATION INSTRUCTIONS:

#### Surface Preparation

1. Plasterboard, fibrous cement sheeting, particleboard and timber must be fixed in accordance with manufacturers' directions.
2. Contaminants such as grease, oil, wax dirt, dust, loose particles, paint, plaster-droppings and any other contaminant must be removed prior to applying. Cement render must be allowed to dry for at least 7 days and concrete for at least 28 days. Particleboard must be sanded prior to application.

#### Application

1. Apply onto the correctly prepared surface using a brush, roller or sponge. Allow to dry for at least 15 minutes prior to the application of adhesive or waterproofing membrane.

### P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

### HEALTH AND SAFETY

- This product is of low toxicity, however, ingestion or contact with the eyes should be avoided.
- Splashes in the eye may cause irritation.
- Prolonged skin exposure may cause slight irritation.

### CLEAN UP

Clean tools and equipment with warm water and detergent before product dries.

### PRECAUTIONS

#### Limitations

- Only suitable on porous surfaces
- Do not use on non-porous surfaces such as existing tiles, waterproofing membranes or steel trowel finished floors.

**BOSTIK INSTANT PRO™ PRIMER**

ITEM NO.	Barcode	Stock	Ctn Qty
293547	9310492442341	1 Litre	6
293555	9310492442358	5 Litre	4

*The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Findley Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.*

**ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK FINDLEY AUSTRALIA PTY LTD**

**FOR FURTHER INFORMATION**

**BOSTIK FINDLEY AUSTRALIA PTY LTD**  
Phone: +61-3-9279 9333  
Fax: +61-3-9279 9240

**BOSTIK FINDLEY NZ LIMITED**  
Phone: +64-4-567 5119  
Fax: +64-4-567-5412

**BOSTIK FINDLEY SINGAPORE PTE LTD**  
Phone: +65-6863 4088  
Fax: +65-6863 4077

**BOSTIK FINDLEY (MALAYSIA) SDN BHD**  
Phone: +606 764 3246  
Fax: +606 764 3248

**SYDNEY**  
Phone: 02 8825 3488  
Fax: 02 8825 3411

**ADELAIDE**  
Phone: 08 8244 0511  
Fax: 08 8244 0522

**PERTH**  
Phone: 08 9331 7666  
Fax: 08 9331 7677

**BRISBANE**  
Phone: 07 3265 2377  
Fax: 07 3265 5421

**(ABN 79 003 893 838)**

Product:	Bostik Instant-Pro™ Primer
Issue Date:	June 2003
Issue No:	1
Division:	Hardware