

technical data sheet

BOSTIK INSTANT-PRO™ SKIRTING BOARD ADHESIVE

PRODUCT

Bostik Instant-PRO™ Skirting Board Adhesive bonds MDF, vinyl, and plastic skirting to plasterboard, concrete, timber, metal and rubber.

Bostik Instant-PRO™ Skirting Board Adhesive is recommended for most types of vinyl and plastic skirtings, coverstrips, plastic and metal stair treads and hosing.

It is also ideal for fixing laminated plastics (Laminex Formica etc) table tops, benches and cupboard doors.

Bostik Instant-PRO™ Skirting Board Adhesive is a high solids, high heat resistant, non-stringing solvent based glue. It is fast drying with early bond strength.

RECOMMENDED USES

Because of the wide range of surfaces and floorings, a test of any new combination should be conducted before using. Not recommended for polystyrene, copper or for external use.

FEATURES & BENEFITS

- Packaging is easy to read and follow
- Fast drying
- High early bond strength
- Suitable for most plastic and vinyl skirting

PROPERTIES

Appearance	Thin clear liquid with solvent odour
Colour	Clear
Chemical Type	Solvent Based Adhesive, High Solids
Specific Gravity	0.81g / cm ³
Working Temperature	5°C to 50°C
Tack Free Working Time	15-20 minutes, depending upon conditions
Coverage	Approximately 4-5m ² per litre on one surface
Cure Time	Full Cure 3-7 days
Shelf Life	Minimum of 12 months from date of manufacture. Store in cool, dry place.

PACKAGING

Bostik Instant-PRO™ Skirting board Adhesive is available in 1L, and 4L containers.

APPLICATION INSTRUCTIONS

Preparation

Ensure the surface is clean, even and free of dust, dirt and old paint, A very porous surface should be primed first with Bostik Instant-PRO™ Priming Fluid.

Application

1. Thoroughly stir adhesive before use.
2. Make sure the area you are applying adhesive to is clean and dry.
3. Apply an even film of adhesive with a roller coater to both surfaces to be bonded, paying particular attention to the edges.
4. Allow to dry until touch dry. This will take approximately 10-15 minutes, depending on atmospheric conditions.

Note – To test if surface is touch dry, place knuckles onto the adhesive coat, which should feel tacky, but not transfer onto the knuckles.

5. Ensure surfaces are positioned correctly and then press two surfaces together.
6. An instant bond will occur, however maximum bond strength will be achieved after 48 hours.
7. Surface should be joined within 45 minutes. If after the time a thin layer of adhesive will reactivate the adhesive. A minimum pressure of 276 kPa is recommended for best results.

HEALTH AND SAFETY

Use only in well ventilated areas. Highly flammable.

Bostik Instant PRO™ Skirting Board Adhesive must be stored and used away from sparks and open flame. Avoid contact with eyes and skin.

Wear solvent resistant gloves, and safety glasses with side shields.

Avoid breathing vapours respirator when spraying or where ventilation is inadequate.

A Material Safety Data sheet is available on request.

PRECAUTIONS

- Wear Solvent resistant gloves.
- Test a small area, before applying product to surfaces.

STORAGE

Minimum of 12 months from date of manufacture if stored under cover between 5°C and 30°C

BOSTIK INSTANT-PRO™ SKIRTING BOARD ADHESIVE

Item No	Barcode	Size	Carton Qty
293989	9310492442730	1 L	6
293997	9310492442747	4 L	4

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Findley Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK FINDLEY AUSTRALIA PTY LTD

FOR FURTHER INFORMATION



BOSTIK FINDLEY
AUSTRALIA PTY LTD
Phone: +61-3-9279 9333
Fax: +61-3-9279 9240

BOSTIK FINDLEY
NZ LIMITED
Phone: +64-4-567 5119
Fax: +64-4-567-5412

BOSTIK FINDLEY
SINGAPORE PTE LTD
Phone: +65-6863 4088
Fax: +65-6863 4077

BOSTIK FINDLEY
(MALAYSIA) SDN BHD
Phone: +606 764 3246
Fax: +606 764 3248

SYDNEY
Phone: 02 8825 3488
Fax: 02 8825 3411

ADELAIDE
Phone: 08 8244 0511
Fax: 08 8244 0522

PERTH
Phone: 08 9331 7666
Fax: 08 9331 7677

BRISBANE
Phone: 07 3265 2377
Fax: 07 3265 5421

(ABN 79 003 893 838)

Product:	Bostik Instant PRO Skirting Board Glue
Issue Date:	June, 2003
Issue No:	1
Division:	Hardware